



SCP SERIES

Horizontal, Double Suction
Split-Case Inline Pumps





EBITT was born from “an idea” and turned into “an ideal”

EBITT is a specialized organization with deep expertise in pump and fluid technologies, capable of accurately interpreting both Turkish and global market demands and translating them into the right solutions.

Founded to be the ideal intersection of supply and demand in fluid technologies, EBITT goes beyond developing and marketing products. It represents a holistic business model built to meet expectations at the highest level.

More than a company, EBITT is a perspective, a system, and a spirit. Its foundation is human capital and accumulated expertise, transferred sustainably like a relay race rather than treated as a traditional capital asset.

For EBITT, innovation is not limited to technological advancement. It is a creative, value-driven approach that prioritizes responsibility, customer expectations, business efficiency, and uncompromising standards for health and safety. Every innovation emerges from this integrated understanding.

Quality, for EBITT, is a non-negotiable standard in all areas involving water and fluids—throughout life. Together with its suppliers, customers, and team members who share this philosophy, EBITT builds long-term, sustainable win-win relationships.

With this mindset, EBITT offers a wide range of products and systems, from basic solutions to process-specific equipment, serving residential, industrial, agricultural, irrigation, pool, treatment, and specialized applications. Beyond standard products, EBITT also delivers tailor-made solutions that maximize added value.

EBITT believes the ideal solution is not always the most expensive one, but the most rational—optimizing needs in the most efficient way.

Positioning itself as a trusted solution provider, EBITT stands out with its values, flexibility, and dynamic structure, ready to respond to evolving demands.

SCP SERIES

HORIZONTAL, DOUBLE SUCTION
SPLIT-CASE INLINE PUMPS



Construction

Single-stage horizontal centrifugal pumps, with suction and discharge flanges on the same axis. Split case design allows disassembly of pump hydraulic parts without disassembling suction and discharge flanges.

Double suction impeller design increases suction performance and balances axial forces on impeller and shaft.

Rated speed of rotation (50 Hz):

SCP = 2900 l/min.

SCP4 = 1450 l/min.

SCP6 = 960 l/min.

Connections: PN 16 / PN 25 flanges EN 1092-2.

Max. working pressure 16 (25) bar

Shaft sealing

- Standardized mechanical seal in accordance with ISO 3069.
- Stuffing box seal or different mechanical seals (on request).

Applications

- For clean liquids, without abrasives, which are non-aggressive for the pump materials (contents of solids up to 0.2 %).
- For water supply.
- For heating, air conditioning, cooling and circulation plants.
- For civil and industrial applications and for agriculture.
- For fire fighting applications.
- For irrigation.

Operating Conditions

- Liquid temperature from -10°C to + 120°C. (standard mechanical seal)
- Ambient temperature up to 40°C.
- Total suction lift up to 7 m.
- Maximum permissible working pressure up to 16/25 bar.

Materials

Pump casing	GG25
Sealing box	(Optional GGG 40 I AISI304 / AISI316 I Bronze)
Bearing housing	
Impeller	
Pump shaft	AISI 420 (Optional AISI 304 I AISI 316)
Wear rings	Bronze (Optional AISI304 I AISI316)
Mechanical seal	Silicon Carbide I Carbon Graphite*
Baseplate	DIN 17100 - St 37, epoxy coated
Coupling guard	EN 294 I DIN 31001, epoxy coated

* Different mechanical seals or soft gland packings are available upon request.

Pump-Motor unit

SCP, SCP4, SCP6 pump connected to a standard electric motor in B3 construction form (IEC 72), IP 54 protection, threephase 400 V, 50 Hz by means of a baseplate, driven by a flexible coupling and with coupling protection.

Special Features On Request

- Special mechanical seal.
- Different construction materials for specific applications.
- Higher or lower liquid or ambient temperatures.
- Other motor protection.
- Explosion proof motor.
- Motor for other voltage.
- Frequency 60 Hz (as per 60 Hz data sheet).



EBITT EUROPE KFT

H-6782 Mórahalom, Szegedi út 108. Hungary Phone: +3662-280-926

Fax: +3662-280-927

export@ebitteurope.com

www.ebitteurope.com



EBITTME PUMPS ENGINES VALVES & SPARE

PARTS TRADING CO. L.L.C.

ALSUAIDI, Al Suwaidi Bldg, Al Murar - Deira

P.O. Box 453929 Dubai, UAE

emea@ebitteurope.com

+971 55-454 4187



**EBITT FINDUSTRIE (ZHE JIANG) INDUSTRIAL
ENGINEERING LIMITED COMPANY**

Hangzhou City, Zhejiang Province, China

info@ebitt.com.cn

+86 15168651662

EBITT ASIA PACIFIC PTE LTD

(EAP Singapore)

226 Jalan Eunos #04-128. Singapore 415869 Phone: (65) 98393745

info@ebitt-asiapac.com

EBITT TÜRKİYE

Koçullu Mah. Doğru Sok. No:6 34799 Çekmeköy / İstanbul

info@ebitt.com.tr

www.ebitt.com.tr